

# MATERIAL SAFETY DATA SHEET

prepared 01/21/03

## HAZARDS IDENTIFICATION

### (ANSI Section 3)

**Primary route(s) of exposure :** Inhalation, skin contact, eye contact, ingestion.

#### Effects of overexposure :

**Inhalation :** Irritation of respiratory tract, lungs. Prolonged inhalation may lead to mucous membrane irritation, fatigue, drowsiness, dizziness and/or lightheadedness, headache, nausea, chest pain, coughing, central nervous system depression, difficulty of breathing, severe lung irritation or damage, kidney damage, pneumoconiosis. Possible sensitization to respiratory tract.

**Skin contact :** Irritation of skin. Prolonged or repeated contact can cause dermatitis, defatting, severe skin irritation. Possible sensitization to skin.

**Eye contact :** Irritation of eyes. Prolonged or repeated contact can cause conjunctivitis.

**Ingestion :** Ingestion may cause mouth and throat irritation, drowsiness, dizziness and/or lightheadedness, headache, nausea, vomiting, diarrhea, gastro-intestinal disturbances, severe abdominal pain, apathy, central nervous system depression, respiratory problems, intoxication, kidney damage, pulmonary edema, convulsions, loss of consciousness, acute poisoning, respiratory failure, cardiac failure, brain damage.

**Medical conditions aggravated by exposure :** Eye, skin, respiratory disorders lung disorders asthma-like conditions kidney disorders respiratory disorders

## FIRST-AID MEASURES

### (ANSI Section 4)

**Inhalation :** Remove to fresh air. Restore and support continued breathing. Get emergency medical attention. Have trained person give oxygen if necessary. Get medical help for any breathing difficulty. Remove to fresh air if inhalation causes eye watering, headaches, dizziness, or other discomfort.

**Skin contact :** Wash thoroughly with soap and water. If any product remains, gently rub petroleum jelly, vegetable or mineral/baby oil onto skin. Repeated applications may be needed. Remove contaminated clothing. Wash contaminated clothing before re-use.

**Eye contact :** Flush immediately with large amounts of water, especially under lids for at least 15 minutes. If irritation or other effects persist, obtain medical treatment.

**Ingestion :** If swallowed, obtain medical treatment immediately.

## FIRE-FIGHTING MEASURES

### (ANSI Section 5)

**Fire extinguishing media :** Dry chemical or foam water fog. Carbon dioxide. Closed containers may burst if exposed to extreme heat or fire. May decompose under fire conditions emitting irritant and/or toxic gases. In closed tanks, water or foam may cause foaming or eruption.

**Fire fighting procedures :** Water may be used to cool and protect exposed containers. Firefighters should use full protective clothing, eye protection, and self-contained breathing apparatus. Self-contained breathing apparatus recommended.

**Hazardous decomposition or combustion products :** Carbon monoxide, carbon dioxide, toxic gases. Acrylic monomers sodium oxide.

## ACCIDENTAL RELEASE MEASURES

### (ANSI Section 6)

**Steps to be taken in case material is released or spilled :** Comply with all applicable health and environmental regulations. Eliminate all sources of ignition. Ventilate area. Spills may be collected with absorbent materials. Evacuate all unnecessary personnel. Place collected material in proper container. Complete personal protective equipment must be used during cleanup. Large spills - shut off leak if safe to do so. Dike and contain spill. Pump to storage or salvage vessels. Use absorbent

to pick up excess residue. Keep salvageable material and rinse water out of sewers and water courses. Small spills - use absorbent to pick up residue and dispose of properly.

## HANDLING AND STORAGE

### (ANSI Section 7)

**Handling and storage :** Store below 100°F (38°C). Keep away from heat, sparks and open flame. Keep from freezing.

**Other precautions :** Use only with adequate ventilation. Do not take internally. Keep out of reach of children. Avoid contact with skin and eyes, and breathing of vapors. Wash hands thoroughly after handling, especially before eating or smoking. Keep containers tightly closed and upright when not in use. Avoid conditions which result in formation of inhalable particles such as spraying or abrading (sanding) painted surfaces. If such conditions cannot be avoided, use appropriate respiratory protection as directed under exposure controls/personal protection. Empty containers may contain hazardous residues.

## EXPOSURE CONTROLS/PERSONAL PROTECTION (ANSI Section 8)

**Respiratory protection :** Control environmental concentrations below applicable exposure standards when using this material. When respiratory protection is determined to be necessary, use a NIOSH/MSHA (Canadian z94.4) Approved elastomeric sealing-surface facepiece respirator outfitted with organic vapor cartridges and paint spray (dust/mist) prefilters. Determine the proper level of protection by conducting appropriate air monitoring. Consult 29CFR 1910.134 for selection of respirators (Canadian z94.4).

**Ventilation :** Provide dilution ventilation or local exhaust to prevent build-up of vapors.

**Personal protective equipment :** Eye wash, safety shower, safety glasses or goggles. Impervious gloves, impervious clothing, face shield.

## STABILITY AND REACTIVITY

### (ANSI Section 10)

**Under normal conditions :** Stable see section 5 fire fighting measures

**Materials to avoid :** Oxidizers, acids, bases, hydrofluoric acid, hydrogen fluoride, mineral acids, hydroxyl containing compounds. Nitrates.

**Conditions to avoid :** Elevated temperatures, contact with oxidizing agent, freezing, sparks, open flame.

**Hazardous polymerization :** Will not occur

## TOXICOLOGICAL INFORMATION

### (ANSI Section 11)

**Supplemental health information :** Contains a chemical that may be absorbed through skin. Excessive inhalation of fumes may lead to metal fume fever characterized by a metallic taste in mouth, excessive thirst, coughing, weakness, fatigue, muscular pain, nausea, chills and fever. Other effects of overexposure may include toxicity to liver, kidney, lungs, reproductive system.

**Carcinogenicity :** Contains crystalline silica which is considered a hazard by inhalation. IARC has classified crystalline silica as carcinogenic to humans (group 1). Crystalline silica is also a known cause of silicosis, a noncancerous lung disease. The national toxicology program (NTP) has classified crystalline silica as a known human carcinogen. The international agency for research on cancer (IARC) has classified carbon black as possibly carcinogenic to humans (group 2b) based on sufficient evidence in animals and inadequate evidence in humans. The international agency for research on cancer (IARC) has classified cobalt and certain cobalt compounds as possibly carcinogenic to humans (group 2b). Injection of metallic cobalt, cobalt alloys, and certain cobalt compounds has resulted in the development of localized tumors in laboratory animals.

The information contained herein is based on data available at the time of preparation of this data sheet which ICI Paints believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. ICI Paints shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use. Complies with OSHA hazard communication standard 29CFR1910.1200.

AMERICAS FINEST EXTERIOR LATEX FLAT  
ICI Paints North America 925 Euclid Avenue Cleveland, Ohio 44115  
EMERGENCY TELEPHONE NO. (800) 545-2043

HM30XX

**Reproductive effects :** A study conducted by NTP, using a continuous breeding protocol, demonstrated that diethylene glycol in drinking water at a concentration of 3.5% (6.1 G/kg/day) resulted in decreased fertility and reproductive performance in mice. These effects were not seen in the lower dose levels evaluated. Since the exposure resulting from incidental contact is likely to be lower by several degrees of magnitude and the route of exposure used in this study does not reflect a likely route from occupational or consumer use the significance of these findings to humans is uncertain.

**Mutagenicity :** No mutagenic effects are anticipated.

**Teratogenicity :** Some laboratory test results have shown ethylene glycol to be an animal teratogen.

## ECOLOGICAL INFORMATION

### (ANSI Section 12)

No ecological testing has been done by JCI paints on this product as a whole.

## Physical Data

### (ANSI Sections 1, 9, and 14)

Product Code	Description	Wt. / Gal.	VOC gr. / ltr.	% Volatile by Volume	Flash Point	Boiling Range	HMIS	DOT, proper shipping name
HM 3000	glidden america's finest exterior latex flat house paint - white (also tint base)	11.58	84.00	68.61	none	100-105	110	paint ** protect from freezing **
HM 3009	glidden america's finest exterior latex flat house paint - sandstone	11.13	78.45	67.77	none	212-401	*210	paint ** protect from freezing **
HM 3010	america's finest latex flat house paint - ultra bright white	10.84	83.88	74.41	none	212-212	110	paint ** protect from freezing **
HM 3011	america's finest exterior latex flat house paint - base 1	11.58	83.88	68.62	none	100-105	110	paint ** protect from freezing **
HM 3012	america's finest exterior latex flat house paint - base 2	10.26	52.91	64.16	none	100-105	110	paint ** protect from freezing **
HM 3015	america's finest latex flat house paint redwood	10.68	65.90	63.87	none	212-383	*210	paint ** protect from freezing **
HM 3018	glidden america's finest exterior latex flat house paint - pastel tint base	10.64	83.88	74.41	none	212-212	110	paint ** protect from freezing **
HM 3023	glidden america's finest exterior latex flat house paint - heritage	11.00	86.04	68.12	none	212-401	*210	paint ** protect from freezing **
HM 3024	glidden america's finest exterior latex flat house paint - white	11.68	83.88	68.61	none	100-105	110	paint ** protect from freezing **
HM 3037	america's finest latex flat house paint oxford	10.84	82.66	61.66	none	212-383	*210	paint ** protect from freezing **
HM 3079	glidden america's finest exterior latex flat house paint - black	9.83	84.30	70.69	none	212-383	*210	paint ** protect from freezing **
HM 3080	glidden america's finest exterior latex flat house paint - deep tint base	10.16	82.44	59.52	none	212-383	*210	paint ** protect from freezing **
HM 3087	america's finest latex flat house paint intermediate tint base	10.33	88.44	62.92	none	212-383	*210	paint ** protect from freezing **
HM 3090	glidden america's finest exterior latex flat house paint - accent tint base	10.66	70.94	59.94	none	212-401	*210	paint ** protect from freezing **

## Ingredients

### Product Codes with % by Weight (ANSI Section 2)

Chemical Name	Common Name	CAS. No.	HM 3000	HM 3009	HM 3010	HM 3011	HM 3012	HM 3015	HM 3018	HM 3023	HM 3024	HM 3037	HM 3079	HM 3080	HM 3087	HM 3090
1,2-ethanediol	ethylene glycol	107-21-1		1-5						1-5		1-5			1-5	
ethanol, 2,2'-oxybis-	diethylene glycol	111-46-6						1-5				1-5		1-5	1-5	
zinc oxide	zinc oxide	1314-13-2		1-5						1-5		1-5				
iron oxide	iron oxide	1332-37-2						5-10			.1-1.0		.1-1.0	1-5		
carbon black	carbon black	1333-BB-4									1-5					
silicate acid, aluminum sodium salt	sodium alumino-silicate	1344-00-9	1-5				1-5								5-10	
titanium oxide	titanium dioxide	13463-67-7	10-20	10-20	10-20	10-20	1-5	1-5	10-20	10-20	10-20				5-10	
cristobalite	crystalline silica, cristobalite	14484-46-1						1-5				1-5	1-5			1-5
quartz	quartz	14808-60-7							10-20				20-30	10-20		20-30
2-propenoic acid, butyl ester, polymer with ethenyl acetate	vinyl acrylic latex	26067-01-0	5-10				5-10	20-30			5-10					
propanoic acid, 2-methyl-1-monocarboxylic ester with 2,2,4-trimethyl-1,3-pentanediol	texanol	23265-77-4	1-5			1-5	1-5			1-5	1-5	1-5		1-5		1-5
nepheline syenite	feldspar-type minerals	37244-96-5	10-20	5-10	10-20	10-20	10-20		10-20	5-10	10-20			10-20	10-20	
naphthenic acids, cobalt salts	cobalt naphthenate	81789-51-3		.1-1.0					.1-1.0		.1-1.0		.1-1.0	.1-1.0	.1-1.0	
Kieselguhr	diatomaceous earth, uncalcined	61790-53-2		1-5	1-5					1-5	1-5			5-10	1-5	
ceramic materials and wares, chemicals	celadon kaolin clay	66402-60-4	5-10	1-5	1-5	5-10	5-10		1-5	1-5	5-10			5-10	1-5	

## DISPOSAL CONSIDERATIONS

### (ANSI Section 13)

**Waste disposal :** Dispose in accordance with all applicable regulations. Avoid discharge to natural waters.

## REGULATORY INFORMATION

### (ANSI Section 15)

As of the date of this MSDS, all of the components in this product are listed (or are otherwise exempt from listing) on the TSCA inventory. This product has been classified in accordance with the hazard criteria of the CPR (controlled products regulations) and the MSDS contains all the information required by the CPR.

## Ingredients (Continued)

## Product Codes with % by Weight (ANSI Section 2)

Chemical Name	Common Name	CAS. No.	HM 300D	HM 3009	HM 3010	HM 3011	HM 3012	HM 3015	HM 3018	HM 3023	HM 3024	HM 3037	HM 3079	HM 3080	HM 3087	HM 3090
fatty acids, tall-oil, polymers with isophthalic acid and pentaerythritol	alkyd resin	67749-05-8		1-5				1-5		1-5		1-5	1-5	5-10	1-5	
kieselgur, soda ash flux, calcined	silica, diatomaceous earth	68855-54-9						1-5				1-5	1-5			1-5
water	water	7732-18-5	40-50	40-50	50-60	40-50	40-50	40-50	50-60	40-50	40-50	40-50	50-60	40-50	40-50	40-50
Acrylic resin	acrylic resin	Sup. Conf.		5-10	5-10			10-20	5-10	5-10		10-20	10-20	10-20	10-20	10-20

## Chemical Hazard Data

## (ANSI Sections 2, 8, 11, and 15)

Common Name	CAS. No.	ACGIH-TLV			OSHA-PEL			S.R. Std.	S2	S3	CC	H	M	N	I	O			
		8-Hour TWA	STEL	C	S	8-Hour TWA	STEL	C	S										
ethylene glycol	107-21-1	not est.	not est.	100 mg/m <sup>3</sup>	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	y	y	y	n	n	n
diethylene glycol	111-46-6	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	n	n	n
zinc oxide	1314-13-2	5 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	not est.	not est.	5 mg/m <sup>3</sup>	not est.	not est.	not est.	not est.	not est.	not est.	n	y	n	n	n	n	n
iron oxide	1332-37-2	5 mg/m <sup>3</sup>	not est.	not est.	not est.	10 mg/m <sup>3</sup>	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	n	n	n
carbon black	1333-86-4	3.5 mg/m <sup>3</sup>	not est.	not est.	not est.	3.5 mg/m <sup>3</sup>	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	y	n
sodium aluminosilicate	1344-00-9	10 mg/m <sup>3</sup>	not est.	not est.	not est.	5 mg/m <sup>3</sup>	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	n	n
titanium dioxide	13463-67-7	10 mg/m <sup>3</sup>	not est.	not est.	not est.	10 mg/m <sup>3</sup>	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	n	n
crystalline silica, cristobalite	14464-46-1	0.05 mg/m <sup>3</sup>	not est.	not est.	not est.	0.05 mg/m <sup>3</sup>	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	y	y	n
quartz	14808-60-7	.05 mg/m <sup>3</sup>	not est.	not est.	not est.	0.1 mg/m <sup>3</sup>	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	y	y	n
vinyl acrylate latex	26087-01-0	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	n	n
texanol	25285-77-4	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	n	n
feldspar-type minerals	37244-96-5	5 mg/m <sup>3</sup>	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	hot est.	n	n	n	n	n
cobalt naphthenate	51789-51-3	.02 mg/m <sup>3</sup>	not est.	not est.	not est.	.1 mg/m <sup>3</sup>	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	n
diatomaceous earth, uncalcined	61790-53-2	10 mg/m <sup>3</sup>	not est.	not est.	not est.	6 mg/m <sup>3</sup>	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	y	a	y	n	y
calcined kaolin clay	66402-68-4	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	n
silica, diatomaceous earth	68855-54-9	10 mg/m <sup>3</sup>	not est.	not est.	not est.	6 mg/m <sup>3</sup>	not est.	not est.	not est.	not est.	not est.	not est.	not est.	not est.	n	n	n	n	n

### Footnotes:

C=Ceiling - Concentration that should not be exceeded, even instantaneously.

S=Skin - Additional exposure, over and above airborne exposure, may result from skin absorption.

n/a=not applicable  
not est.=not established  
CC=CERCLA Chemical

ppm=parts per million  
mg/m<sup>3</sup>=milligrams per cubic meter  
Sup Conf=Supplier Confidential

S2=Sara Section 302 EHS  
S3=Sara Section 313 Chemical  
S.R.Std.=Supplier Recommended Standard

H=Hazardous Air Pollutant, M=Marine Pollutant  
P=Pollutant, S=Severe Pollutant  
Carcinogenically Listed By:  
N=NTP, I=IARC, D=OSHA, y=yes, n=no